



Optiview Pro 8.4" LCD monitor

- Instrument quality waveform including Luma and RGB Parade, 3 mode vectorscope.
- HD-SDI / SDI input with active loop-through.
- Advanced marker settings with multiple frame markers and look-around shading.
- Industry standard knobs for easy adjustment of brightness, contrast, tint, audio volume.
- Accurate reproduction of interlaced HD Image.
- 100% pixel for pixel zoom for critical focus assist.
- Color Temperature / Gamma Selection.
- Wide color gamut for top image quality.
- Contrast enhanced panel with 170° wide viewing angle and custom shield for protection.
- Daylight viewable.
- AC/DC operation and onboard battery mount.
- Rugged industrial strength metal case, rack mountable, high quality finish.
- Swiveling metal base.

Options

- Mounting bracket mini C-stand compatible
- Waterproof case



Specifications:

Model name	OVP-9-SDI
LCD type	A-SI TFT Active Matrix
Picture size	8.4 inch diagonal
Pixels displayed	1024 x 768
Aspect ratio	4 x 3
Aspect marker	Selectable
Area marker	Selectable
16x9 / 4x8 capability	Selectable
Colors displayed	16.7M
Color Temperature/Gamma selection	Selectable
Viewing angle (typ)	170/170
Contrast ratio (typ)	600:1
Brightness	400 nits
Tally	2 colors

Input / Output

Composite	BNC x 2 with output
Y/C	DIN x2 with output
Audio	RCA x 4 Dual channel stereo with loop through
RGB/Component (Y.R-Y,B-Y)	BNC x 4
HD-SDI /DI-SDI	BNC x 4 (2xHD or SD Auto detect)

Remote

Parallel remote control	RJ-45 modular connector (Pin assignment user selectable)
-------------------------	--

Internal speakers

Speaker output power	3.1W + 3.1W - Stereo
Frequency range	140Hz - 20KHz

Power

Power requirement	AC 100V-240V 50/60Hz or DC10-24V
Li-Ion battery	Selectable

General

Power consumption	Approx. 30W
Operating temperature	0°C - 40°C
Operation humidity	30% to 85% (No condensation)
Storage & Transport temperature	-10°C to 40°C
Storage & Transport humidity	0% to 90%
Operation/Storage/Trans. Pressure	700hpa to 1060hpa
Dimensions (WxHxD) mm	218 x 207 x 89
With stand and base	218 x 240 x 89
Supplied Accessories	AC adaptor, AC cord, Manual, Warranty card, Regular Certificate.